

TECHNICAL DATA SHEET

Supatexprime

Preparation primer for Render and Texture coat systems to supaboard panels.

Supatexprime is light weight aggregate filled single pack, non-toxic, water-based sealer used on Supaboard panels prior to the application of render or texture systems..

Note: For application of a painted finish only to Supaboard panels use Supaprime

TECHNICAL DATA

SOLIDS CONTENT VISCOSITY VOC (VOLATILE ORGANIC CONTENT) SPECIFIC GRAVITY WATER SENSITIVITY HIGH TEMPERATURE STABILITY **FILM APPEARANCE** FILM FORMING TEMPERATURE PARTICLE SIZE WEIGHT AVERAGE STORAGE

APPLICATION

COVERAGE

RECOMMENDED APPLICATION RATE SAFETY

45% +/- 2% 25 Poise < 5.0 g/l 0.8 Kg/Ltre Very Low (1 week at 50 Deg C) Very Good Off white granulated liquid + 5º C 20 microns In fully sealed containers to avoid skin forming By roller

Laboratory tested at 25 Deg C 4-5 m2/Litre @ 20 microns Dry Film Thickness (D.F.T.) 4 m2/Litre Non Hazardous, water based Wash with water if contacted with skin or eyes

AREAS OF APPLICATION:

Supaprime has high adhesion to Supaboard panels and porous surfaces. Can be applied in any conditions above freezing temperature and to damp surfaces.

Uniseal Manufacturing is part of the



17 Ryelane Street Maddington WA 6109 Ph: 1300 577 719 Fax: 1300 366 353 Email: uniseal@sealingservices.com.au www.global-services.com.au

Date Of Issue:

Revision No.

2