

UNISEAL MANUFACTURING

ABN: 52 189 407 505

Phone: 1300 577 719

Fax: (08) 9458 3655

E: uniseal@sealingservices.com.au

46 John Street, Bentley, W.A. 6102

www.global-services.com.au www.mortastic.com.au

TECHNICAL DATA SHEET

Supaprime

Sealer for Supaboard, Concrete, Gyprock, Masonry, Fibro-cement and Aluminium surfaces.

Supaprime is a single pack, non-hazardous, non-toxic, water-based sealer and binding agent formulated for use on a variety of substrates. Supaprime is based on special waterbased adhesion promoted resins and additives, specifically designed for sealing Supaboard panels, Concrete, Gyprock, Masonry, Fibro cement, Aluminium and other surfaces.

TECHNICAL DATA

SOLIDS CONTENT	25% +/- 2%
VISCOSITY	2.0 Poise
VOC (VOLATILE ORGANIC CONTENT)	< 5.0 g/l
SPECIFIC GRAVITY	1.020 +/- 0.005 Kg/Litre
WATER SENSITIVITY	Very Low
HIGH TEMPERATURE STABILITY	(1 week at 50 Deg C) Very Good
FILM APPEARANCE	Light Green
FILM FORMING TEMPERATURE	+ 5° C
STORAGE	In fully sealed containers to avoid skin forming
APPLICATION	By airless spray equipment, brush or roller
COVERAGE	Laboratory tested at 25 Deg C 8-14 m2/Litre @ 20 microns Dry Film Thickness (D.F.T.)
RECOMMENDED APPLICATION RATE	10 m2/Litre
SAFETY	Non Hazardous, water based Wash with water if contacted with skin or eyes

AREAS OF APPLICATION:

*Supaprime has high adhesion to Supaboard panels and porous surfaces. Can be applied in any conditions above freezing temperature and to damp surfaces.

*Mask exposed glass surfaces to avoid overspray, as product may be difficult to remove

*By applying two or more coatings, deep penetration and binding of other porous or fibrous substrates can be achieved in this regards.

Uniseal Manufacturing is part of the



46 John Street Bentley WA 6102

Ph: 1300 577 719

Fax: 08 9458 3655

Email: uniseal@sealingservices.com.au

www.global-services.com.au

Date Of Issue: 28/1/2011

Last Revision: 28/1/2011

Revision No.

2